
## [High Precision] Dovetail Slide, Feed Screw Long (Selectable lead) / Compact Carriage (Lead 4.2mm)



30 XLSL 14.7 29.4 120 22.5 80 0.16 ±57 150 25 110 40 40 0.18


Plesolution (Vernier Scale Indication): 0.1mm/division

\*\*Nob Cover HDCVH; Scold Separately): 015 knobs can be increased in diameter by installing the cover. 


\*\*PRODE Plate XPLT40: Use this plate when connecting stages with non-matching mounting holes. 

\*\*P1915\*\*





## [High Precision] X-Axis Dovetail Slide, Feed Screw / [Simplified Adjustments] X-Axis Rack & Pinion Compact Carriage, Low Profile (Lead 4.2mm) / Standard



Part Number		Stage Surface			Load Capacity (N) Travel Accu					Accessory		Unit Price
Type	No.	(mm)	(mm)	Rotation (mm)	Horizontal	Vertical	Straightness	Parallelism	(kg)	Type M-L	Qty.	Office Price
XSSLC	40	24.8x42	±12	4.2	19.6	9.8	30	30	0.08	SCB4-6	4	


Resolution (Vernier Scale Indication): 0.1mm/division


Extension Cover HDcYT12 (Sold Separately): 612 feed screw knob can be extended. 

Reparately: 612 feed s









	Part Number		Stage Surface	Travel Distance	В	v	В	Load Capacity	Weight	Unit Price	
	Туре	No.	(mm)	(mm)	В	^	F	(N)	(kg)	XKRG	XKRKG
	XKRG XKRKG	40	25x40	±12	25	31	-	29.4	0.10		
		60	40x60	±14	40	45	15	39.2	0.21		
		90	40x90	±23		75			0.30		

Travel per Rotation: Approx. 19mm Minimum Graduation: 0.5mm

