

Shaft Supports L-Shaped (Machined)

Standard / Slit

■ **Features** : Suitable when crosswise space is limited. For Standard Type, the most economical price is placed. For Slit Type, the shafts can be secured without damage.

■ **Standard**

Height H Selectable Type	Height H Configurable Type	Material	Surface Treatment	Accessory
SHKLB	SHKLBH	S45C Equivalent	Black Oxide	Hex Socket Head Cap Screw 1 pc. Set Screw 1 pc.
SHKLM	SHKLMH	SUS304	Electroless Nickel Plating	Hex Socket Head Cap Screw 1 pc. Set Screw 1 pc. (SUS)
SHKLS	SHKLSH	-	-	-
SHKLA	SHKLAH	Aluminum Alloy	Clear Anodize	-

Part Number	H														Unit Price			
	Type	D	Height H Selectable Type	Height H Configurable Type	L	H ₁	T	S	W	W ₁	Set Screw M	L ₁	d	Height H Selectable Type	Height H Configurable Type			
Height H Selectable Type	3	10	15	20	20	H+5	6	4	14	10	M3	10	3.6	SHKLB	SHKLBH			
	4	10	15	20										SHKLM	SHKLMH			
	5	15	20	25										SHKLS	SHKLSH			
	6	15	20	25										SHKLA	SHKLAH			
	8	15	20	25										30	40	SHKLB	SHKLBH	
	10	20	25	30										40	SHKLM	SHKLMH		
Height H Configurable Type	12	20	25	30	40	25	H+8	8	6	18	13	M4	13	4.5	SHKLS	SHKLSH		
	13	20	25	30	40										SHKLA	SHKLAH		
	16	20	25	30	40										SHKLB	SHKLBH		
	20	25	30	40	50										60	SHKLM	SHKLMH	
	25	30	40	50	60										SHKLS	SHKLSH		
	30	35	40	50	60										SHKLA	SHKLAH		
	35	40	50	60	SHKLB										SHKLBH			
	40	40	50	60	80										SHKLM	SHKLMH		
	40	40	50	60	80										SHKLS	SHKLSH		
	50	50	60	80	SHKLA										SHKLAH			

■ **Slit Type**

Height H Selectable Type	Height H Configurable Type	Material	Surface Treatment	Accessory
SHKSB	SHKSBH	S45C Equivalent	Black Oxide	Hex Socket Head Cap Screw 1 pc.
SHKSM	SHKSMH	SUS304	Electroless Nickel Plating	Hex Socket Head Cap Screw 1 pc. (SUS)
SHKSS	SHKSSH	-	-	-
SHKSA	SHKSAH	Aluminum Alloy	Clear Anodize	Hex Socket Head Cap Screw 1 pc.
SHKSD	-	-	Black Anodize	Hex Socket Head Cap Screw 1 pc.

Part Number	H														Unit Price						
	Type	D	Height H Selectable Type	Height H Configurable Type	L	H ₁	T	S	W	W ₁	Set Screw M	L ₁	d	Height H Selectable Type	Height H Configurable Type						
Height H Selectable Type	3	10	15	20	20	H+11	8	4	16	12	12	3.5	7	M3	3.5	3.5	1.5	SHKSB	SHKSBH		
	4	10	15	20														SHKSM	SHKSMH		
	5	15	20	25														SHKSS	SHKSSH		
	6	15	20	25														SHKSA	SHKSAH		
	8	15	20	25														30	40	SHKSB	SHKSBH
	10	20	25	30														40	SHKSM	SHKSMH	
Height H Configurable Type	12	20	25	30	40	25	H+16	10	6	20	15	4.5	11	M4	4.5	8	4.5	SHKSS	SHKSSH		
	13	20	25	30	40													SHKSA	SHKSAH		
	16	20	25	30	40													SHKSB	SHKSBH		
	20	25	30	40	50													60	SHKSM	SHKSMH	
	25	30	40	50	60													SHKSS	SHKSSH		
	30	35	40	50	60													SHKSA	SHKSAH		
	35	40	50	60	SHKSB													SHKSBH			
	40	40	50	60	80													SHKSM	SHKSMH		
	40	40	50	60	80													SHKSS	SHKSSH		
	50	50	60	80	SHKSA													SHKSAH			

Ordering Example: Part Number - H
 SHKLM8 - 25
 SHKLMH8 - 25.6

Shaft Supports L-Shaped (Machined)

Side Slit / Split

■ **Features**: Suitable when crosswise space is limited. Side Slit Type allows each screw to be fixed from above. Split Type facilitates maintenance.

■ **Side Slit**

Height H Selectable Type	Height H Configurable Type	Material	Surface Treatment	Accessory
SHKWB	SHKWBH	S45C Equivalent	Black Oxide	Hex Socket Head Cap Screw 1 pc.
SHKWM	SHKWMH	SUS304	Electroless Nickel Plating	Hex Socket Head Cap Screw 1 pc. (SUS)
SHKWS	SHKWSH	-	-	-
SHKWA	SHKWAH	Aluminum Alloy	Clear Anodize	Hex Socket Head Cap Screw 1 pc.
SHKWD	-	-	Black Anodize	Hex Socket Head Cap Screw 1 pc.

Part Number	H														Unit Price					
	Type	D	Height H Selectable Type	Height H Configurable Type	L	H ₁	T	S	W	W ₁	Set Screw M	L ₁	d	Height H Selectable Type	Height H Configurable Type					
Height H Selectable Type	8	15	20	25	30	40	10	6	22	16	22	4.5	11	M4	4.5	8	4.5	2	SHKWB	SHKWBH
	10	20	25	30	40	SHKWM													SHKWMH	
	12	20	25	30	40	SHKWS													SHKWSH	
	13	20	25	30	40	SHKWA													SHKWAH	
	16	20	25	30	40	SHKWB													SHKWBH	
	20	25	30	40	50	60													SHKWM	SHKWMH
Height H Configurable Type	25	30	40	50	60	16	8	32	24	36	6.5	17	M6	6.6	11	6.5	3	2	SHKWS	SHKWSH
	30	40	50	60	SHKWA														SHKWAH	
	35	40	50	60	SHKWB														SHKWBH	
	40	40	50	60	80														SHKWM	SHKWMH
	40	40	50	60	80														SHKWS	SHKWSH
	40	40	50	60	80														SHKWA	SHKWAH

■ **Split**

Height H Selectable Type	Height H Configurable Type	Material	Surface Treatment	Accessory
SHKPB	SHKPBH	S45C Equivalent	Black Oxide	Hex Socket Head Cap Screw 2 pcs.
SHKPM	SHKPMH	SUS304	Electroless Nickel Plating	Hex Socket Head Cap Screw 2 pcs. (SUS)
SHKPS	SHKPSH	-	-	-
SHKPA	SHKPAH	Aluminum Alloy	Clear Anodize	Hex Socket Head Cap Screw 2 pcs.
SHKPD	-	-	Black Anodize	Hex Socket Head Cap Screw 2 pcs.

Part Number	H														Unit Price							
	Type	D	Height H Selectable Type	Height H Configurable Type	L	H ₁	T	S	W	W ₁	Set Screw M	L ₁	d	Height H Selectable Type	Height H Configurable Type							
Height H Selectable Type	3	10	15	20	22	H+6	8	4	16	12	13	3.5	13	M3	3.5	6.5	3.5	1.5	SHKPB	SHKPBH		
	4	10	15	20															SHKPM	SHKPMH		
	5	15	20	25															SHKPS	SHKPSH		
	6	15	20	25															SHKPA	SHKPAH		
	8	15	20	25															30	40	SHKPB	SHKPBH
	10	20	25	30															40	SHKPM	SHKPMH	
Height H Configurable Type	12	20	25	30	40	30	H+10	10	6	20	15	26	4.5	M4	4.5	8	4.5	2	SHKPS	SHKPSH		
	13	20	25	30	40														SHKPA	SHKPAH		
	16	20	25	30	40														SHKPB	SHKPBH		
	20	25	30	40	50														60	SHKPM	SHKPMH	
	25	30	40	50	60														SHKPS	SHKPSH		
	30	30	40	50	60														SHKPA	SHKPAH		
	35	40	50	60	SHKPB														SHKPBH			
	40	40	50	60	80														SHKPM	SHKPMH		
	40	40	50	60	80														SHKPS	SHKPSH		
	50	50	60	80	SHKPA														SHKPAH			

Ordering Example: Part Number - H
 SHKWS20 - 30
 SHKPSH20 - 30.6

ex Example
 Combination of these app. examples can be selected on the Web.
 Details about Selection Procedure **P87**

e-Catalog Search Keyword
 #MA822 Search

* Enter the search keyword in the search box on e-Catalog. The search result will be shown in "Modular Assembly" area.