

Tubes

Note that, for some of the types shown here, order might be unable to be received by the MISUMI Malaysia, Indonesia and/or India offices.

Tube Clips / Tube Cutter

**Fluoro Rubber Tubes
Transparent Type**
PUTFB
PUTFBL

Material: Fluoro Rubber

Part Number	Standard Length (m)	Configurable Length (0.5m Increment)	I.D. (mm)	O.D. Accuracy (mm)	Max. Operating Pressure (MPa)	Burst Pressure (MPa)	Mass (kg/m)	Standard		Configurable Length	
								Unit Price	Volume Discount Rate	Unit Price/m	Volume Discount Rate/m
PUTFB (Standard Length)	4	10	2	±0.15	0.248	0.993	0.018	1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	6	20						1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	8	20						1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	10	20						1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
PUTFBL (Configurable Length)	4	10	2	±0.15	0.248	0.993	0.018	1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	6	20						1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	8	20						1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	10	20						1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10

Features: Excellent in transparency and chemical resistance.

**Fluoro Rubber Tubes
Heat Resistant Type**
PUTFG
PUTFGL

Material: Fluoro Rubber

Part Number	Standard Length (m)	Configurable Length (0.5m Increment)	I.D. (mm)	Min. Bending Radius (mm)	O.D. Accuracy (mm)	Max. Operating Pressure (MPa)	Burst Pressure (MPa)	Mass (kg/m)	Standard		Configurable Length	
									Unit Price	Volume Discount Rate	Unit Price/m	Volume Discount Rate/m
PUTFG (Standard Length)	4	10	2	20	±0.15	-	-	0.019	1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	6	20							1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	8	20							1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	10	20							1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
PUTFGL (Configurable Length)	4	10	2	20	±0.15	-	-	0.019	1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	6	20							1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	8	20							1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	10	20							1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10

Features: Excellent in heat resistance (~ 200°C), oil resistance, ozone resistance, and chemical resistance.

Silicon Tubes
PUTC
PUTCL

Material: Silicon Rubber

Part Number	Standard Length (m)	Configurable Length (0.5m Increment)	I.D. (mm)	Min. Bending Radius (mm)	Mass (kg/m)	Standard		Configurable Length	
						Unit Price	Volume Discount Rate	Unit Price/m	Volume Discount Rate/m
PUTC (Standard Length)	4	10	2	10	0.011	1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	6	20				1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	8	20				1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	10	20				1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
PUTCL (Configurable Length)	4	10	2	10	0.011	1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	6	20				1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	8	20				1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10
	10	20				1 ~ 4 pc(s)	5 ~ 10	1 ~ 4 pc(s)	5 ~ 10

Ordering Example: Part Number - Length
PUTFB4 - 10
PUTCL4 - 3.5

Tube Clips

RoHS10

Type	Material	Surface Treatment
CUCLP	SPCC	Trivalent Chromate
CUCLPS	SUS304D	-

Dimensions in () are for CUCLPS.

Part Number	Number of Tubes	A	Applicable Tube O.D. (D)	Unit Price	
				CUCLP	CUCLPS
CUCLP CUCLPS	4	4x pcs.	4		
	6	6x pcs.	6		
	8	8x pcs.	8		
	10	10x pcs.	10		
	12	12x pcs.	12		

Ordering Example: Part Number CUCLP4

Soft Tube Inserts

RoHS10

Type	Material	Surface Treatment
PUIT	C2700T	Electroless Nickel Plating
PACK-PUSIT	SUS304	-

Part Number	Applicable Tube O.D. (mm)	Applicable Tube I.D. (mm)	D	d	D1	L	PUIT		PACK-PUSIT	
							Unit Price	Volume Discount Rate	Unit Price	Volume Discount Rate
PUIT PACK-PUSIT	4	2.5	2.5	2.1	2.8	18	1 ~ 9 pc(s)	10~30	1 ~ 2 pack(s)	3~10
	6	4	4.0	3.6	4.5	18.5				
	8	5	5.0	4.6	5.5	20				
	10	6.5	6.5	6.1	7.0	22				

10 pcs. per pack for PACK-PUSIT.
Features:
• Prevents shrinkage of tube from inside.
• Insert this into the connecting part of soft tubes.

Ordering Example: Part Number PUIT4

Tube Cutter
TCK

Tube Cutter Replacement Blade
TCKE

RoHS10

TCK

Chevron blade
Strap Mounting Hole

Part Number	Unit Price
Type	1 ~ 20 pc(s)
TCK	

Part Number	Quantity	Unit Price
Type	1 ~ 10 pc(s)	
TCKE	10 pcs. / set	

Features:
• New edges can be used by turning the chevron blade 180 degrees.
• The tube can be cut at a desired length using the built-in measure.
• The tube cutter can be safely stored using the lock mechanism.

Ordering Example: Part Number TCK