INSIDE ARROWS FOR PL EXCHANGE TYPE

OUTSIDE RINGS FOR PL EXCHANGE TYPE



Non JIS material definition is listed on P.1351 - 1352

uniform

divisions

10

uniform

divisions

uniform

divisions

uniform

divisions

uniform

Day

Day

Day


DTEX-R

TGX-


16



-STANDARD • SHALLOW ARROW MARK TYPE-




| | ■Year Type | | | | | | | | | | | |
|------------|------------|---------|-----------------|-----|--|-------------|---|--|--|--|--|--|
| Indication | | iontion | Part Num | ber | Year | U/Price 1∼9 | | | | | | |
| | | ication | Туре | No. | rear | DYYX DYYXU | Ĺ | | | | | |
| | | | | | 18 for 2018 | | | | | | | |
| Year | | 1 1 5 | | 5 | ※Days to ship will be 5-days for the adjustment of production after November 2018. | | | | | | | |
| | | | D 100/ | 6 | It is scheduled to close sales in April 2019 | | | | | | | |
| | ਰ | | DYYX | 8 | 19 for 2019 (available from Sept., 2018) **Days to ship will be 5-days for the adjustment of production | | i | | | | | |
| | Ē | | DYYXU | 10 | after November 2019. It is scheduled to close sales in April 2020 | | İ | | | | | |
| | | | (Shallow arrow) | 12 | 20 for 2020 (available from Sept.,2019) | | | | | | | |
| | | | | 16 | ※ Days to ship will be 5-days for the adjustment of production after November 2020. | | | | | | | |
| | | | | 20 | It is echadulad to close cales in April 2021 | | | | | | | |



The inside arrows are the same with those of overall length adjustable type.













■ Character Designation Type

| Indication | | Part Number | er | Engraving characters (2 characters • Characters printed in blue in indications) | U/Price |
|--------------|----------------|-------------|-----|---|---------|
| | | Туре | No. | Engraving characters (2 characters • Characters printed in blue in indications) | 1~9 |
| | | | 4 | Name Characters for engaving Order code | |
| 2 Characters | | DYMX | 5 | A B C D E Slash / ¥ | ō |
| | | | 6 | FGHIJ Greater > > | ¥[|
| | (A 1 B) | | 8 | 0 1 2 3 4 K L M N O Less < < | |
| | | | 10 | U V W X Y Plus + + | 의 의 |
| | | | 12 | Z Minus — # | |
| | | | 16 | Space []] % | |

- ? 2 characters can be engraved on the inside arrow.
- Use ¥ for indicating ∠(slash), # for —(minus), and % for ;;; (space).
- The inside arrows are the same with those of overall length adjustable type



Order


Part Number — Characters for engraving — AB



Quotation



Quotation



Days to ship will be 5-days for the adjustr

It is scheduled to close sales in April 2021

Days to ship will be 5-days for the adjustme

of production after November 2020.

of production after November 2018. It is scheduled to close sales in April 2019

for 2019 (available from Sept., 2018)

of production after November 2019.

for 2020 (available from Sept. 2019)

of production after November 2020

Days to ship will be 5-days for the adjustr

It is scheduled to close sales in April 2021

Days to ship will be 5-days for the adjustress
 The ship will be 5-days for the adjustress to ship will be 5-days for the 5-days for the adjustress to ship will be 5-days for the 5-days for th

It is scheduled to close sales in April 2020





DTXS-F



for 2018

16

10





uniform

divisions

■Character Designation Type

| Indication | | | | | | | | | | | | | | |
|--------------------|--------------------|--------------------|--------------------|---|--|--|------------------------|--|--|--|--|--|--|--|
| 1M (1 place) | 2M (2 places) | 3M (3 places) | 4M (4 places) | 5M (5 places) | 6M (6 places) | 10M (10 places) | 12M (12 places) | | | | | | | |
| Engraving position | Engraving position | Engraving position | Engraving position | Engraving position | Engraving position | Engraving position | Engraving position | | | | | | | |
| (NZ) | (ABS) | © (POM) | © AS TO O | PA PO PA PA PO PA | (b) (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c | O Outside ring is divided equally among ten. | | | | | | | | |

Up to 3 characters can be designated at each engraving position. Up to 2 characters can be designated at each engraving position. Only 1 character can be designated at each engraving position.

| Pa | rt Numbe | Engraving characters (1~3 characters • Characters printed in blue in indications) | | | | | | U/Price 1~9 | | | | | | | | | | | |
|------|------------|---|---|------------------------|---|---|---|-------------|-----------------------|---|--|--|--|----|-----|-------|-----|-----|-----|
| Type | Indication | D | | Engraving position ①~⑫ | | | | | | | | | | 3M | 4M | 5M | 6M | 10M | 12M |
| | 1M | 4 | 0 | 1 | 2 | 3 | 4 | Name | Characters Order code | | | | | | | _ | - | _ | |
| | 2M | 5 | 5 | 6 | 7 | 8 | 9 | Slash | for engraving | V | | | | | | _ | _ | _ | |
| DTX | 3M | 6 | A | В | C | Þ | Ę | Greater > > | | | | | | | | | | | |
| _ | 5M ** | 4M 5M % | K | L | М | N | Ö | Less | < | < | | | | | Quo | tatio | on) | | |
| -R | 6M X | 10 | P | ā | R | S | Ť | Plus | + | + | | | | _ | | | | | |
| | 10M * | 12 | U | V | W | X | Υ | Minus | _ | # | | | | | | | | | |
| | 12M | 16 | Z | | | | | Space | | % | | | | | | | | | |

• Use ¥ for indicating ✓ (slash), # for — (minus), and% for ;; (space) is Not applicable to D4 and D5 of 5M, 6M and 10M.



DTX-R 10M16 - 1

Part Number



